

5GFlex®28 Assemblies

5G Flex Assemblies are dependable and flexible, outdoor rated, general-use coaxial cable assemblies fitting for many 5G applications. Utilizing Times Microwave's cable heritage, these assemblies will withstand the test of time while providing reliable electrical performance.

Cable


Diameter	0.205"	5.21 mm
Diameter	0.203	J.Z1111111
Minimum Bend Radius	0.5"	12.7 mm
Operating Temperature	-40° F to 185° F -40° C to 85° C	
Weight	0.03 lbs/ft	
	0.04 kg/	m ′m

Electrical Properties

Maximum Frequency	28 GHz	
Impedance	50 ohms	
Capacitance	26.9 pF/ft	88.23 pF/m
Velocity of Propagation	75.5%	
Delay	1.35 ns/ft	4.42 ns/m
Shielding	>90 dB	



- Assembly VSWR of 1.2 typical / 1.4 max up to 28 GHz
- Small minimum bend radius
- Flexible polyurethane jacket
- IP67 rated



- 1 Shrink Tubing
- 2 Label
- 3 Label
- 4 Shrink Tubing
- 5 Length

Attenuation	dB/ft	dB/m
2500 MHz	0.19	0.62
5800 MHz	0.30	0.98
28000 MHz	0.74	2.42

5GFlex® 28

Ordering Guide

